



WHEELED LOADING SHOVELS | MILITARY VARIANTS

Engine power: 36.4 - 216 kW (49 - 290 hp) Operating weight: 4,934 - 23,800 kg Standard shovel capacity: 0.8 - 4.0 m³

 **JCB**
GOVERNMENT & DEFENCE

MILITARY LOADERS.

1 JCB's first military machines were articulated steer loaders fitted with forks instead of shovels. In total nearly 1,000 JCB 410M models were supplied to the UK MoD beginning in 1984. 30 years on, articulated wheeled loaders like the 436M are still popular with military users.

2 Our wheeled loading shovels offer superb loader performance. Several configurations are available to improve reach, tearout or fork lifting.

3 These wheeled loaders offer a versatile and robust solution for military applications. In medium wheeled tractor trim, they've been used extensively by the UK Army to support beach landing operations.

4 A militarised JCB wheeled loading shovel can be waterproofed for a 1.5m wading depth. It can also be winterised for operating in temperatures as low as -40°C.

5 The optional chassis-mounted front winch is ideally suited to recovery operations, while a roof hatch improves access.

3



2



4



1

COMMERCIAL RANGE.



409



411 / 417



427 / 437



436M



457



467

SPECIFICATION

	406 / 407	409	411 / 417	427 / 437	436M*	457	467
Operating weight	kg	5020 / 5210	6031	8688 / 9425	13053 / 15255	14503	19302
Power	kW	36.4 / 48	55.4	81 / 93	118 / 129	132	186
Length	mm	5133	5465	6229 / 6290	6831 / 6926	6926	8542
Width over tyres	mm	1390	1490	2204 / 2328	2482 / 2597	2597	2702
Standard shovel size	m ³	0.8	1.0	1.4 / 1.6	2.4 / 2.7	2.4	3.5
Max. tearout force	kN	41.9	53.8	67.7 / 64.6	123 / 135	147	143

Notes:

Figures are for standard machine with bucket and hitch using HT arms.

Performance and dimensions may change depending on configuration.

* Non-T4i compliant.



9999/5563 07/14 en-GB Issue 2



WHEELED LOADING SHOVELS | MILITARY VARIANTS

Engine power: 36.4 - 216 kW (49 - 290 hp) Operating weight: 4,934 - 23,800 kg Standard shovel capacity: 0.8 - 4.0 m³

J C Bamford Excavators Ltd., Defence Products, Rocester, Staffordshire, ST14 5JP England

Tel +44 (0)1889 590312

©2009 JCB Sales. All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form or by any other means, electronic, mechanical, photocopying or otherwise, without prior permission from JCB Sales. All references in this publication to operating weights, sizes, capacities and other performance measurements are provided for guidance only and may vary dependant upon the exact specification of machine. They should not therefore be relied upon in relation to suitability for a particular application. Guidance and advice should always be sought from your JCB Dealer. JCB reserves the right to change specifications without notice. Illustrations and specifications shown may include optional equipment and accessories. The JCB logo is a registered trademark of J C Bamford Excavators Ltd.

JCB
GOVERNMENT & DEFENCE